


LAMP PHOTOMETRIC REPORT

MODEL: 95EL229145W/WH		
POWER: 45W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 3488.4 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1138	1136	1135	1135	1136	1138	1140	1140	0- 10	109.5	109.5	3.14
20	1081	1077	1074	1074	1077	1080	1084	1084	10- 20	314.1	423.6	12.1
30	987.2	982.0	976.8	977.4	982.2	986.6	991.3	991.9	20- 30	477.5	901.1	25.8
40	861.3	854.7	848.3	849.1	855.3	860.6	866.5	867.4	30- 40	578.6	1480	42.4
50	709.3	701.5	694.2	695.1	702.3	708.2	714.9	716.2	40- 50	605.0	2085	59.8
60	538.2	530.1	522.3	523.2	530.7	536.5	544.0	545.4	50- 60	555.4	2640	75.7
70	358.7	350.9	343.1	343.6	350.8	356.4	363.7	365.3	60- 70	439.6	3080	88.3
80	187.6	180.5	173.2	175.8	181.3	186.3	192.7	193.4	70- 80	282.0	3362	96.4
90	61.58	58.27	55.26	54.74	58.25	62.66	64.76	64.96	80- 90	126.8	3488	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 31 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```