TECHNICAL SPECIFICATION



BASES FOR HIGH POWER SAFETY DEVICES




The series bases for high power safety device is manufactured of permitivity alloy with mounted contact jaws of electrolytic copper supplied with special springs for contact compression and easy fuse links taking out. All current leading parts are connected to inlet outlet terminals with bolts; the terminals also end with bolts, to which the power supply conductors are connected. The bases are offered in five type sizes corresponding to the five types of fuse links.

1 | Page

TECHNICAL SPECIFICATION



Dimensions:



Dimensions

(mm)

Base type	A1	A2	А3	B1	B2	C1	C2	Ød
SIST00	25	100	120	-	30	25	60	7.5
SIST 0	25	150	170	-	30	37	72	7.5
SIST1	25	175	200	30	58	38	84	10.5
SIST2	25	200	225	30	60	38	100	10.5
SIST3	25	210	250	30	60	40	105	10.5

2 | Page

TECHNICAL SPECIFICATION The Brand of Electricity



Basic data:



Base type	Fuse link type	Rated current (A)	Rated voltage Un (V)	Weight (gr)	Packing/ Box (pcs)	Catalogue number
SIST00	NT 00	Up to 160	600	193	5/120	12001
SISP00	NT 00	Up to 160	600	215	5/120	12001P

^{*}Remark: Fuse bases SIST are made of resin



Base type	Fuse link type	Rated current (A)	Rated voltage Un (V)	Weight (gr)	Packing/ Box (pcs)	Catalogue number
SISTO	NT 0	Up to 160	600	295	3/54	12010
SISP0	NT O	Up to 160	600	319	3/54	12010P

^{*}Remark: Fuse bases SIST are made of resin

3 | Page elmarkholding.eu

^{*}Remark: Fuse bases SISP are made of porcelain

^{*}Remark: Fuse bases SISP are made of porcelain

TECHNICAL SPECIFICATION The Brand of Electricity





Base type	Fuse link type	Rated current (A)	Rated voltage Un (V)	Weight (gr)	Packing/ Box (pcs)	Catalogue number
SIST1	NT 1	Up to 250	600	550	3/36	12100
SISP1	NT 1	Up to 250	600	550	3/36	12100P

^{*}Remark: Fuse bases SIST are made of resin

^{*}Remark: Fuse bases SISP are made of porcelain



Fuse link type	Rated current (A)	Rated voltage Un (V)	Weight (gr)	Packing/ Box (pcs)	Catalogue number
NT 2	Up to 400	600	770	1/20	12200
NT 2	Up to 400	600	810	1/20	12200P
	type NT 2	type current (A) NT 2 Up to 400	type current voltage (A) Un (V) NT 2 Up to 400 600	type current voltage (gr) (A) Un (V) NT 2 Up to 400 600 770	type current voltage (gr) (pcs) (A) Un (V) NT 2 Up to 400 600 770 1/20

^{*}Remark: Fuse bases SIST are made of resin *Remark: Fuse bases SISP are made of porcelain

4 | Page elmarkholding.eu

TECHNICAL SPECIFICATION The Brand of Electricity





Base type	Fuse link type	Rated current (A)	Rated voltage Un (V)	Weight (gr)	Packing/ Box (pcs)	Catalogue number
SIST3	NT 3	Up to 630	600	965	1/20	12300
SISP3	NT 3	Up to 630	600	987	1/20	12300P

^{*}Remark: Fuse bases SIST are made of resin

Standards:

EN 60269-1



5 | Page elmarkholding.eu

^{*}Remark: Fuse bases SISP are made of porcelain