


LAMP PHOTOMETRIC REPORT

MODEL: 92EL62284230/WH		
POWER: 42W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 4082.8 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2404	2397	2394	2396	2402	2409	2413	2410	0- 10	233.1	233.1	5.71
20	2186	2175	2169	2172	2184	2196	2200	2198	10- 20	649.5	882.6	21.6
30	1712	1691	1677	1678	1702	1721	1733	1733	20- 30	907.7	1790	43.8
40	1107	1088	1074	1073	1091	1111	1125	1125	30- 40	871.4	2662	65.2
50	605.9	591.2	581.2	580.3	591.1	605.3	616.4	617.3	40- 50	642.3	3304	80.9
60	306.4	300.8	296.2	295.5	299.8	305.0	306.6	310.4	50- 60	385.2	3689	90.4
70	181.9	176.5	169.9	173.4	177.5	178.1	176.1	181.5	60- 70	235.3	3924	96.1
80	75.11	69.59	63.03	67.66	70.93	69.07	68.41	70.74	70- 80	127.3	4052	99.2
90	1.258	1.215	1.180	1.237	1.093	1.100	1.071	1.085	80- 90	30.97	4083	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 05 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

