

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	5314.2 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	61.7V x 61.5H
	At 50% of Imax	33.2V x 33.3H
	At 90% of Imax	13.2V x 13.5H

Beam Flux	Total	2034.2 lumens per klm.
	To 10% of Imax	1838.9 lumens per klm.
	To 50% of Imax	1005.6 lumens per klm.
	To 90% of Imax	209.2 lumens per klm.

Upward LOR	0.0 %
Downward LOR	203.4 %


Luminaire Efficiency (Light Output Ratio)	202.9 %
---	---------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	93M20TL0540/BL	Imax (cd)	797.1
NOMINAL POWER (W)	5	AVAILABILITY (%)	183.3
RATED VOLTAGE (V)	48	Avai. FLUX (lm)	274.9
NOMINAL FLUX (lm)	150	LOR (%)	202.9
LAMPS INSIDE	1	TOTAL FLUX (lm)	304.4
TEST VOLTAGE (V)	48	θ @50% (H,V)	33,33DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00
40	0.00	0.00	0.00	0.00	0.00	0.01	0.07	0.15	0.22	0.23	0.15	0.06	0.01	0.00	0.00	0.00	0.00	0.00	0.91	0.00
30	0.00	0.00	0.00	0.00	0.01	0.11	0.40	0.92	1.37	1.31	0.84	0.35	0.09	0.01	0.00	0.00	0.00	0.00	5.42	0.28
20	0.00	0.00	0.00	0.00	0.05	0.36	1.41	3.35	5.13	4.91	3.04	1.22	0.30	0.04	0.00	0.00	0.00	0.00	19.8	15.9
10	0.00	0.00	0.00	0.00	0.11	0.83	3.29	8.22	13.0	12.4	7.19	2.69	0.65	0.10	0.00	0.00	0.00	0.00	48.4	45.7
0	0.00	0.00	0.00	0.01	0.16	1.24	5.09	13.3	21.0	20.0	11.4	3.99	0.93	0.13	0.01	0.00	0.00	0.00	77.2	74.9
-10	0.00	0.00	0.00	0.01	0.17	1.25	5.18	13.6	21.4	20.3	11.4	4.00	0.94	0.13	0.01	0.00	0.00	0.00	78.4	76.1
-20	0.00	0.00	0.00	0.01	0.12	0.84	3.42	8.49	13.3	12.4	7.08	2.59	0.62	0.09	0.00	0.00	0.00	0.00	48.9	46.2
-30	0.00	0.00	0.00	0.00	0.05	0.35	1.48	3.44	5.08	4.80	2.85	1.11	0.28	0.04	0.00	0.00	0.00	0.00	19.5	15.5
-40	0.00	0.00	0.00	0.00	0.01	0.09	0.36	0.88	1.30	1.23	0.73	0.30	0.08	0.01	0.00	0.00	0.00	0.00	5.00	0.22
-50	0.00	0.00	0.00	0.00	0.00	0.01	0.05	0.13	0.19	0.17	0.10	0.05	0.01	0.00	0.00	0.00	0.00	0.00	0.71	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.00	0.00	0.00	0.03	0.67	5.08	20.7	52.5	82.0	77.6	44.8	16.4	3.91	0.56	0.03	0.00	0.00	0.00	304	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.64	17.0	49.6	79.2	74.8	41.7	11.9	0.00	0.00	0.00	0.00	0.00	0.00	---	275

one-half-peak spread: U:16.8,D:16.7 , L:17.9,R:15.6


NEMA Beam Type: Type 4

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 09 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 09 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

AAI Figure

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:
 Test Date:09 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-65	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.02	0.02	0.04	0.04	0.02
-55	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.02	0.04	0.10	0.14	0.16	0.18	0.18	0.16
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.05	0.10	0.15	0.28	0.51	0.91	1.18	1.31	1.32
-45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.05	0.16	0.23	0.61	1.50	2.76	4.10	4.98	5.36	5.27
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.03	0.14	0.32	1.06	2.59	4.77	7.51	10.4	13.5	15.0	14.8
-35	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.04	0.11	0.25	1.15	2.96	6.09	10.9	18.2	27.2	35.6	40.0	41.2
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.06	0.18	0.75	2.91	6.41	12.9	25.7	42.9	61.0	76.6	85.3	88.3
-25	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.11	0.34	1.79	5.40	11.8	26.5	50.7	81.8	113	143	162	172
-20	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.16	0.63	3.25	8.50	20.2	45.6	83.6	132	189	245	284	290
-15	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.17	1.17	4.65	11.8	30.3	65.6	120	194	287	380	446	456
-10	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.16	1.63	5.90	15.8	40.2	83.8	155	260	390	521	613	634
-5	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.14	1.80	6.53	17.9	46.3	97.2	183	312	471	629	735	761
0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.12	1.78	6.68	18.3	47.9	101	189	326	497	663	772	797
5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.12	1.62	6.33	17.6	45.8	96.0	179	303	460	615	717	743
10	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.12	1.31	5.50	15.3	39.7	83.4	152	251	378	507	595	617
15	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.11	0.90	4.36	11.7	30.2	63.8	115	187	278	370	435	451
20	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.09	0.47	3.03	8.54	20.2	43.3	78.4	125	182	241	283	292
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.22	1.66	5.66	12.6	26.8	47.9	76.1	111	142	169	169
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.10	0.73	3.28	7.56	14.8	26.5	42.2	60.7	77.5	88.9	89.4
35	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.24	1.41	4.04	7.75	12.9	20.3	28.9	37.4	42.7	43.0
40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.10	0.35	1.52	3.54	6.07	9.01	11.8	15.1	17.1	17.7
45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.09	0.24	0.88	2.02	3.39	4.53	5.74	6.52	6.85
50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	0.13	0.28	0.59	1.04	1.50	1.82	1.97
55	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.04	0.08	0.11	0.11	0.13	0.15
60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.01	0.02
65	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:09 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL0540/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-65	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-60	0.03	0.04	0.02	0.01	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-55	0.17	0.16	0.12	0.11	0.10	0.03	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-50	1.10	0.89	0.67	0.41	0.26	0.15	0.10	0.03	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-45	4.64	3.92	3.06	2.24	1.31	0.65	0.24	0.15	0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-40	13.3	11.2	8.39	6.33	4.34	2.55	1.07	0.32	0.11	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-35	37.7	31.2	22.4	15.0	9.72	5.73	3.03	1.09	0.21	0.08	0.03	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-30	84.2	68.3	50.0	33.5	20.6	11.3	5.81	2.66	0.63	0.14	0.04	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-25	153	127	94.1	62.5	37.4	20.4	9.80	4.59	1.46	0.26	0.08	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-20	263	213	155	101	61.5	33.2	15.3	6.79	2.58	0.46	0.12	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-15	414	332	238	152	90.3	48.4	22.0	9.17	3.69	0.85	0.14	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-10	573	458	324	204	118	63.3	29.6	12.0	4.65	1.22	0.17	0.03	0.01	0.00	0.00	0.00	0.00	0.00	
-5	695	557	390	245	140	73.9	34.5	13.8	5.33	1.48	0.19	0.04	0.01	0.00	0.00	0.00	0.00	0.00	
0	735	592	415	260	146	76.9	35.9	14.4	5.64	1.59	0.21	0.04	0.02	0.00	0.00	0.00	0.00	0.00	
5	682	550	391	246	138	72.2	34.1	14.0	5.42	1.47	0.19	0.03	0.01	0.00	0.00	0.00	0.00	0.00	
10	564	456	325	207	120	63.2	30.0	12.4	4.82	1.22	0.17	0.02	0.01	0.00	0.00	0.00	0.00	0.00	
15	412	335	243	157	94.6	49.7	23.6	9.78	3.91	0.89	0.14	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
20	270	220	162	108	66.3	35.2	16.5	7.35	2.79	0.49	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
25	161	130	99.6	68.8	41.4	22.4	10.5	4.89	1.61	0.24	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
30	83.7	72.0	54.7	37.5	23.0	12.5	6.26	2.80	0.66	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
35	40.5	34.6	26.4	18.1	11.1	6.41	3.29	1.16	0.21	0.07	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
40	16.9	14.7	11.2	8.16	5.26	2.90	1.18	0.28	0.10	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
45	6.75	5.98	4.64	3.27	1.79	0.68	0.19	0.07	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
50	2.00	1.73	1.17	0.57	0.25	0.11	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
55	0.16	0.15	0.14	0.11	0.04	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
60	0.01	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
65	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:09 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: