

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	3867.4 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	42.1V x 42.6H
	At 50% of Imax	16.7V x 17.0H
	At 90% of Imax	6.5V x 6.6H

Beam Flux	Total	725.1 lumens per klm.
	To 10% of Imax	468.1 lumens per klm.
	To 50% of Imax	200.1 lumens per klm.
	To 90% of Imax	42.0 lumens per klm.

Upward LOR	0.0 %
Downward LOR	72.5 %

Luminaire Efficiency (Light Output Ratio)	72.1 %
---	--------

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature: 25.3°C

Operators:

Test Date: 01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456


Humidity: 65.0%

Test Distance: 6.265m [K=1.0000]

Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 96GRF1/31524	TYPE: 96GRF1/31524	WEIGHT: 1
SPEC.:	DIM.: F 100 x 80	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	96GRF1/31524	Imax (cd)	1044
NOMINAL POWER (W)	3	AVAILABILITY (%)	46.7
RATED VOLTAGE (V)	230	Avai. FLUX (lm)	126.1
NOMINAL FLUX (lm)	270	LOR (%)	72.1
LAMPS INSIDE	1	TOTAL FLUX (lm)	194.8
TEST VOLTAGE (V)	230	θ @50% (H,V)	17,17DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00
90	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.03	0.03	0.03	0.03	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.22	0.00
80	0.00	0.00	0.00	0.01	0.02	0.04	0.06	0.09	0.10	0.11	0.10	0.08	0.05	0.03	0.01	0.00	0.00	0.00	0.71	0.00
70	0.00	0.00	0.01	0.03	0.06	0.10	0.14	0.18	0.20	0.21	0.21	0.17	0.12	0.06	0.03	0.01	0.00	0.00	1.53	0.00
60	0.00	0.00	0.02	0.05	0.12	0.19	0.28	0.36	0.41	0.43	0.38	0.30	0.21	0.11	0.05	0.02	0.00	0.00	2.93	0.00
50	0.00	0.00	0.03	0.08	0.19	0.33	0.50	0.74	0.95	0.96	0.72	0.48	0.31	0.16	0.07	0.02	0.00	0.00	5.55	0.00
40	0.00	0.01	0.03	0.12	0.26	0.45	0.83	1.55	2.25	2.24	1.56	0.83	0.42	0.21	0.08	0.03	0.01	0.00	10.9	0.57
30	0.00	0.01	0.04	0.14	0.31	0.59	1.42	3.40	6.38	5.85	3.11	1.42	0.58	0.26	0.10	0.03	0.01	0.00	23.6	16.1
20	0.00	0.01	0.05	0.15	0.33	0.71	2.00	6.18	20.3	18.1	5.24	1.94	0.71	0.29	0.11	0.04	0.01	0.00	56.2	50.3
10	0.00	0.01	0.05	0.14	0.32	0.71	1.99	5.88	18.2	15.8	5.17	1.94	0.73	0.29	0.11	0.04	0.01	0.00	51.4	45.4
0	0.00	0.01	0.04	0.13	0.28	0.59	1.40	3.15	5.31	5.11	3.01	1.40	0.60	0.26	0.11	0.04	0.01	0.00	21.4	13.6
-10	0.00	0.01	0.04	0.10	0.21	0.42	0.81	1.42	1.99	1.97	1.42	0.83	0.43	0.22	0.09	0.03	0.01	0.00	10.0	0.10
-20	0.00	0.00	0.03	0.08	0.15	0.27	0.45	0.65	0.80	0.82	0.68	0.49	0.31	0.17	0.08	0.03	0.00	0.00	4.99	0.00
-30	0.00	0.00	0.02	0.05	0.10	0.15	0.24	0.34	0.41	0.44	0.40	0.32	0.21	0.12	0.05	0.02	0.00	0.00	2.89	0.00
-40	0.00	0.00	0.01	0.03	0.06	0.08	0.11	0.15	0.20	0.23	0.23	0.18	0.11	0.06	0.03	0.01	0.00	0.00	1.49	0.00
-50	0.00	0.00	0.00	0.01	0.03	0.04	0.05	0.06	0.08	0.09	0.08	0.07	0.04	0.03	0.01	0.01	0.00	0.00	0.61	0.00
-60	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.17	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.00	0.06	0.37	1.13	2.47	4.73	10.3	24.2	57.7	52.4	22.4	10.5	4.86	2.28	0.94	0.32	0.06	0.00	195	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.00	0.63	16.2	50.6	45.0	13.5	0.24	0.00	0.00	0.00	0.00	0.00	0.00	---	126

one-half-peak spread: U:7.5,D:9.3 , L:9.3,R:7.8

NEMA Beam Type: Type 3

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456


Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

ISOCANDELA DIAGRAM

NAME: 96GRF1/31524	TYPE: 96GRF1/31524	WEIGHT: 1
SPEC.:	DIM.: F 100 x 80	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:01 September 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 96GRF1/31524	TYPE: 96GRF1/31524	WEIGHT: 1
SPEC.:	DIM.: F 100 x 80	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 01 September 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 01 September 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

AAI Figure

NAME: 96GRF1/31524	TYPE: 96GRF1/31524	WEIGHT: 1
SPEC.:	DIM.: F 100 x 80	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature: 25.3°C

Operators:

Test Date: 01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity: 65.0%

Test Distance: 6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF1/31524	TYPE: 96GRF1/31524	WEIGHT: 1
SPEC.:	DIM.: F 100 x 80	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:

Table--1

UNIT: cd

H(DEC) V(DEC)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.00	0.00	0.00	0.01	0.02	0.02	0.01	0.03	0.05	0.04	0.03	0.05	0.06	0.05	0.04	0.03	0.02	0.01	0.00
-80	0.00	0.00	0.00	0.02	0.05	0.06	0.07	0.10	0.14	0.14	0.13	0.16	0.17	0.16	0.15	0.16	0.17	0.16	0.14
-75	0.00	0.00	0.00	0.04	0.09	0.12	0.14	0.22	0.30	0.35	0.40	0.46	0.51	0.53	0.53	0.56	0.59	0.60	0.60
-70	0.00	0.00	0.02	0.07	0.13	0.20	0.30	0.45	0.58	0.70	0.80	0.91	0.99	1.05	1.09	1.18	1.30	1.42	1.53
-65	0.00	0.00	0.04	0.10	0.20	0.35	0.54	0.76	0.98	1.20	1.43	1.61	1.71	1.80	1.96	2.16	2.37	2.56	2.71
-60	0.00	0.00	0.05	0.12	0.30	0.55	0.82	1.14	1.52	1.92	2.19	2.32	2.49	2.72	3.04	3.36	3.68	3.97	4.19
-55	0.00	0.01	0.07	0.20	0.45	0.76	1.12	1.65	2.24	2.61	2.91	3.16	3.57	3.99	4.43	4.98	5.56	6.16	6.71
-50	0.00	0.01	0.09	0.27	0.60	0.97	1.53	2.32	2.95	3.45	3.92	4.42	5.04	5.71	6.63	7.99	9.00	9.85	10.6
-45	0.00	0.02	0.10	0.36	0.74	1.21	2.02	2.97	3.72	4.43	5.15	6.04	7.07	8.68	10.3	11.7	12.8	13.6	14.2
-40	0.00	0.03	0.12	0.45	0.88	1.56	2.55	3.64	4.62	5.65	6.76	8.34	10.1	12.0	14.0	15.5	16.9	17.9	18.4
-35	0.00	0.03	0.15	0.53	1.05	1.90	3.13	4.35	5.57	6.96	8.72	10.6	12.8	15.7	18.8	21.9	23.9	25.4	26.6
-30	0.00	0.04	0.18	0.61	1.22	2.26	3.69	5.02	6.57	8.36	10.6	13.1	16.8	22.0	26.0	30.9	35.3	38.9	40.5
-25	0.00	0.04	0.20	0.68	1.40	2.59	4.23	5.72	7.58	9.71	12.6	16.3	22.4	28.4	37.4	47.2	56.4	62.8	64.9
-20	0.00	0.05	0.22	0.75	1.55	2.94	4.70	6.38	8.60	11.4	14.8	20.0	27.4	37.7	52.1	71.0	91.0	106	110
-15	0.00	0.05	0.23	0.80	1.68	3.24	5.09	7.06	9.56	13.0	16.8	22.7	33.1	49.4	72.3	106	138	165	174
-10	0.00	0.05	0.24	0.84	1.76	3.48	5.43	7.59	10.3	14.1	18.1	25.5	39.0	60.8	96.0	145	218	315	338
-5	0.00	0.05	0.24	0.87	1.81	3.66	5.69	7.95	10.8	14.8	19.0	27.6	43.0	69.3	116	185	356	652	766
0	0.00	0.05	0.24	0.88	1.83	3.74	5.87	8.16	11.1	15.2	19.4	28.0	44.3	72.6	124	207	452	900	1044
5	0.00	0.05	0.24	0.88	1.81	3.60	5.85	8.21	11.3	15.3	19.3	27.2	42.9	69.1	117	196	389	745	876
10	0.00	0.05	0.23	0.86	1.77	3.39	5.72	8.09	11.2	15.1	18.8	25.4	38.9	60.8	98.3	157	249	397	457
15	0.00	0.05	0.22	0.82	1.69	3.11	5.45	7.80	10.8	14.6	17.9	22.8	33.0	49.6	74.8	113	158	193	200
20	0.00	0.05	0.21	0.76	1.59	2.78	4.97	7.38	10.2	13.7	16.4	20.0	26.6	38.8	54.7	75.8	99.0	117	120
25	0.00	0.05	0.19	0.69	1.46	2.44	4.25	6.67	9.49	12.1	15.0	17.8	22.0	29.0	39.5	51.3	63.3	72.9	75.2
30	0.00	0.04	0.17	0.59	1.31	2.18	3.51	5.60	8.26	10.7	13.2	15.8	18.3	22.1	28.6	35.4	41.7	45.2	47.7
35	0.00	0.04	0.15	0.49	1.14	1.89	2.89	4.47	6.75	8.95	11.0	13.1	15.8	17.6	20.5	25.0	28.9	31.7	32.6
40	0.00	0.04	0.12	0.40	0.95	1.61	2.38	3.52	5.26	6.96	8.59	10.4	12.1	14.3	16.0	17.2	18.9	20.2	21.1
45	0.00	0.03	0.11	0.30	0.74	1.32	1.96	2.74	3.92	5.37	6.44	7.63	8.99	9.97	11.2	11.7	12.7	13.2	13.1
50	0.00	0.03	0.10	0.22	0.52	1.02	1.54	2.10	2.88	4.04	4.94	5.54	6.33	7.10	7.75	8.30	8.77	9.12	9.35
55	0.00	0.02	0.08	0.17	0.36	0.72	1.13	1.56	2.05	2.77	3.54	4.14	4.53	4.96	5.50	5.94	6.29	6.58	6.77
60	0.00	0.01	0.07	0.11	0.22	0.44	0.76	1.08	1.40	1.77	2.20	2.70	3.16	3.51	3.78	4.09	4.51	4.78	4.93
65	0.00	0.01	0.06	0.09	0.14	0.26	0.45	0.67	0.87	1.10	1.35	1.61	1.95	2.29	2.66	2.91	3.10	3.28	3.43
70	0.00	0.01	0.04	0.06	0.09	0.15	0.25	0.38	0.51	0.65	0.79	0.96	1.13	1.34	1.60	1.86	2.10	2.18	2.20
75	0.00	0.01	0.03	0.04	0.05	0.09	0.13	0.19	0.26	0.35	0.44	0.51	0.59	0.70	0.80	0.87	0.92	0.95	0.97
80	0.00	0.01	0.02	0.02	0.02	0.05	0.07	0.08	0.09	0.13	0.17	0.22	0.26	0.31	0.36	0.38	0.39	0.41	0.42
85	0.00	0.00	0.01	0.01	0.00	0.01	0.03	0.02	0.02	0.04	0.06	0.06	0.05	0.07	0.09	0.07	0.05	0.06	0.07
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF1/31524	TYPE: 96GRF1/31524	WEIGHT: 1
SPEC.:	DIM.: F 100 x 80	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: 3 Circle	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.03	0.06	0.05	0.04	0.05	0.06	0.05	0.03	0.04	0.05	0.03	0.01	0.02	0.03	0.01	0.00	0.00	0.00	
-80	0.16	0.17	0.17	0.16	0.17	0.18	0.16	0.13	0.13	0.13	0.11	0.08	0.07	0.06	0.03	0.01	0.01	0.01	
-75	0.64	0.66	0.64	0.62	0.60	0.57	0.52	0.46	0.39	0.33	0.24	0.17	0.14	0.10	0.06	0.01	0.01	0.01	
-70	1.59	1.61	1.53	1.43	1.28	1.14	1.01	0.87	0.77	0.64	0.49	0.35	0.24	0.16	0.09	0.03	0.02	0.02	
-65	2.78	2.79	2.72	2.55	2.27	1.98	1.69	1.45	1.24	1.01	0.78	0.57	0.39	0.25	0.13	0.06	0.02	0.02	
-60	4.43	4.64	4.89	4.62	4.12	3.39	2.70	2.20	1.83	1.52	1.17	0.83	0.57	0.35	0.17	0.08	0.02	0.02	
-55	7.43	7.76	7.70	7.30	6.64	5.58	4.34	3.45	2.71	2.27	1.70	1.16	0.78	0.48	0.24	0.10	0.03	0.03	
-50	11.0	11.0	10.7	10.1	9.09	7.82	6.51	5.20	3.98	3.13	2.45	1.59	1.00	0.60	0.31	0.12	0.04	0.04	
-45	14.5	14.3	13.6	12.7	11.7	10.2	8.38	6.82	5.40	4.18	3.08	2.13	1.23	0.74	0.39	0.15	0.05	0.05	
-40	18.4	18.0	17.2	15.9	14.2	12.5	10.3	8.31	6.62	5.06	3.65	2.73	1.58	0.88	0.46	0.17	0.06	0.06	
-35	26.5	25.0	22.1	19.6	17.4	14.8	12.1	9.84	7.76	5.92	4.20	3.03	1.91	1.02	0.52	0.20	0.07	0.07	
-30	39.4	37.2	32.6	27.1	21.7	18.0	14.2	11.3	8.86	6.73	4.82	3.31	2.22	1.14	0.59	0.23	0.07	0.07	
-25	62.4	55.9	47.0	37.7	29.3	22.0	16.8	12.7	10.0	7.45	5.32	3.59	2.47	1.30	0.66	0.26	0.08	0.08	
-20	103	88.8	69.8	52.6	38.7	28.3	19.7	14.4	10.9	8.12	5.70	3.85	2.61	1.43	0.71	0.28	0.08	0.08	
-15	163	133	100	71.3	49.7	34.0	23.1	16.2	11.7	8.67	6.02	4.04	2.73	1.53	0.75	0.29	0.09	0.09	
-10	278	198	135	91.8	59.7	39.1	26.9	18.1	12.5	9.01	6.19	4.17	2.82	1.58	0.78	0.30	0.09	0.09	
-5	533	286	170	107	68.2	43.2	29.0	18.9	13.1	9.17	6.21	4.22	2.87	1.59	0.79	0.30	0.09	0.09	
0	744	348	184	113	70.9	44.2	29.4	18.6	13.3	9.12	6.08	4.19	2.87	1.58	0.80	0.30	0.10	0.10	
5	649	319	169	107	68.5	42.6	28.0	18.3	13.0	8.96	5.89	4.13	2.84	1.56	0.78	0.29	0.09	0.09	
10	356	211	135	93.1	60.7	39.0	25.3	17.5	12.3	8.56	5.59	4.00	2.75	1.52	0.76	0.28	0.09	0.09	
15	175	137	104	73.6	50.1	33.4	22.0	16.5	11.5	8.10	5.22	3.81	2.62	1.44	0.73	0.27	0.09	0.09	
20	111	95.5	74.6	55.2	39.5	26.7	19.2	15.0	10.7	7.46	4.91	3.60	2.43	1.34	0.68	0.25	0.09	0.09	
25	72.5	63.7	52.0	40.4	29.1	21.3	16.8	13.1	9.95	6.50	4.58	3.36	2.19	1.21	0.62	0.23	0.08	0.08	
30	46.8	42.4	36.4	27.6	21.4	17.4	14.3	11.6	8.77	5.78	4.17	3.04	1.94	1.07	0.56	0.21	0.08	0.08	
35	31.8	28.3	23.1	19.9	16.8	14.5	12.2	10.2	7.28	5.07	3.74	2.65	1.66	0.94	0.48	0.18	0.07	0.07	
40	20.3	18.7	16.9	15.3	13.6	12.0	10.5	8.45	6.04	4.31	3.19	2.18	1.41	0.79	0.40	0.16	0.07	0.07	
45	13.7	13.5	12.8	11.8	10.9	9.83	8.40	6.79	4.92	3.51	2.58	1.79	1.16	0.65	0.30	0.14	0.06	0.06	
50	9.63	9.73	9.78	9.28	8.54	7.53	6.43	5.14	3.75	2.75	2.02	1.43	0.91	0.49	0.22	0.12	0.05	0.05	
55	6.95	7.01	6.86	6.55	6.23	5.60	4.83	3.68	2.72	2.07	1.56	1.09	0.66	0.34	0.17	0.11	0.04	0.04	
60	5.02	5.00	4.85	4.65	4.38	3.89	3.17	2.42	1.93	1.50	1.12	0.74	0.41	0.20	0.13	0.09	0.03	0.03	
65	3.46	3.43	3.29	3.08	2.75	2.33	1.88	1.55	1.24	0.96	0.69	0.43	0.23	0.14	0.10	0.07	0.03	0.03	
70	2.13	2.01	1.85	1.66	1.44	1.23	1.06	0.87	0.70	0.50	0.36	0.21	0.14	0.09	0.08	0.05	0.02	0.02	
75	0.96	0.94	0.88	0.81	0.72	0.61	0.52	0.43	0.32	0.21	0.16	0.13	0.09	0.06	0.05	0.03	0.02	0.02	
80	0.40	0.37	0.36	0.34	0.28	0.23	0.19	0.16	0.11	0.08	0.08	0.08	0.05	0.02	0.02	0.02	0.01	0.01	
85	0.07	0.07	0.08	0.09	0.07	0.05	0.05	0.06	0.04	0.01	0.02	0.02	0.01	0.00	0.01	0.01	0.01	0.01	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:01 September 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: