

# EL<sup>®</sup>MARK

The Brand of Electricity

## LED ROAD LIGHT

### ROUTE SMD



#### GENERAL INFORMATION »

- ∴ Power :30W; 50W; 100W; 150W
- ∴ Rated voltage: 100-265V/AC
- ∴ Frequency: 50/60Hz
- ∴ Power supply: Isolated driver
- ∴ Light source: Focus
- ∴ LED type: SMD
- ∴ Color temperature: 5000-5500K
- ∴ Beam angle: 90°
- ∴ Ambient temperature: -35°C÷ +45°C
- ∴ Colour rendering index: Ra > 80
- ∴ Average lifetime: 20 000 hours
- ∴ PF > 0.9
- ∴ Body material: Aluminium
- ∴ Colour body: Dark grey
- ∴ Cover material: PC
- ∴ Protection against dust and moisture: IP65
- ∴ Available in variant with an emergency kit

#### FEATURES »

- ∴ Completely replaces traditional street lamps
- ∴ Ultra- thin design
- ∴ Wide distribution of homogeneous, highly efficient light
- ∴ Economic- low power consumption
- ∴ Repeated switch on/off does not effect the fixture lifespan
- ∴ Instant light at maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration stable body
- ∴ Voltage supply fluctuations do not affect the normal operation of the fixture


## APPLICATION »

- ∴ Roads, High ways.
- ∴ Urban Street, Bridge, Pavement.
- ∴ Square, School, Residential, Park and other outdoor place.
- ∴ Underground Parking Garage, Parking Lot.

## PRODUCT DETAILS »

Catalogue number	Catalogue number with Emergency kit	Watt (W)	Whole fixture lumens (lm)	Colour temp (K)	Beam angle
98ROUTE30SMD	98ROUTE30SMDE	30	3000	5000-5500	90°
98ROUTE50SMD	98ROUTE50SMDE	50	5000	5000-5500	90°
98ROUTE100SMD	98ROUTE100SMDE	100	10000	5000-5500	90°
98ROUTE150SMD	-	150	15000	5000-5500	90°

## DIMENSIONS »



Model	Length (mm)	Width (mm)	Height (mm)
98ROUTE30SMD	130	53	340
98ROUTE50SMD	155	55	390
98ROUTE100SMD	160	65	450
98ROUTE150SMD	170	65	570


## EMERGENCY DRIVER SPECIFICATIONS »



### Technical data:

- ∴ Input voltage: 85-265V AC
- ∴ Battery: 18.5V 8800mAh
- ∴ Emergency switch time: <5s
- ∴ Suitable: for LED lamp with internal driver and power 20-100W
- ∴ Emergency time: 60-120min
- ∴ Working temperature: from -10 to +50°C
- ∴ Size: 290x105x50mm
- ∴ IP44

### Wiring diagram:



ADDITIONAL INFORMATION »

*stell*★*ar* ROUTE SMD  
lighting solutions

---

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

874/2012

Catalogue number	Barcode	Packing/Box (pcs)
98ROUTE30SMD	3800131227676	1/1
98ROUTE50SMD	3800131227683	1/1
98ROUTE100SMD	3800131227690	1/1
98ROUTE150SMD	3800131227706	1/1

